_Published by European Centre for Research Training and Development UK (www.eajournals.org)

CHALLENGES OF RIPENING OF SUGARCANE AT TENDAHO, METAHARA AND WONJI-SHOA SUGAR ESTATES

Netsanet Ayele, Samuel Tegene, Tadesse Negi, Abiy Getaneh, Leul Mengistu, Yohannes Mequanent and Zinaw Dilnesa

Sugar Corporation, Research Directorate, Wonji, P.O.Box 15

ABSTRACT: Ripening in sugarcane refers to an increase in sugar content on a fresh weight basis before commercial harvest. In Ethiopian Sugar Industry ripening of cane especially at the early and late periods of crushing shows a decline against the mid periods of crushing. Thus, an effort was made to show the trend of ripening and associated losses by considering the problem of ripening at Tendaho, Metahara and Wonji-Shoa Sugar Estates. To have concrete information, cane plantation harvest result, meteorological and experimental data were used. Furthermore, reviews about ripening, research and developments of chemical ripeners, conditions and considerations for good response, environmental and economic issues related to ripeners were made. From the trend analysis and experimental data it is concluded that the conventional ripening method by withholding water has draw back in exploiting the maximum attainable recovery potential at Metahara, Wonji-Shoa and Tendaho Sugar Factories. At Wonji-Shoa, the loss in sucrose percent cane from the peak value attained in the crushing months ranged from 0.02 to 0.95 %. Similarly, at Metahara, the deviation in sucrose percent cane from the peak in the crushing moths ranged from 0.32 to 1.10 %. In general, maximum loss in sucrose percent cane was observed in the early and late periods of crushing. Temperature and residual moisture plays an important role in the ripening of cane and the challenge also seems to occur at Finchaa and newly emerging sugar factories located in the lowlands of the country.

KEYWORDS: sucrose, dry-off period, ripening, chemical ripeners, temperature, rainfall, sucrose loss.

INTRODUCTION

Sugarcane (*Saccharum* spp.), a C_4 perennial grass, is a member of the Gramineae family and produces large quantities of disaccharide (sucrose) which is processed and refined into granulated sugar (Anon, ND). Sugarcane's value is determined by the amount of recoverable sugar per weight of cane (Orgeron, 2003). The economic success of sugarcane crops is determined by the accumulation of sucrose (Batta *et al.* 2002). On a weight basis, about three quarters of a sugarcane stem is water (Sundara, 2000). Out of the total weight transported to mill, the proportion of sucrose varies during the crushing period due to the fact that sugarcane is influenced by the soil fertility, irrigation, varieties, weed, pest and disease control, and many other factors including the length of the crushing season (Humbert, 1968). Conventionally, drying-off by withholding irrigation water few weeks before harvesting is exercised to facilitate

_Published by European Centre for Research Training and Development UK (www.eajournals.org)

cane burning and harvesting operation, and somehow improve sucrose content of cane (Singles *et al.*, 2000; James, 2004). However, this practice does not adequately induce sucrose accumulation (Gosnell and Lonsdale, 1974).

Sugarcane ripening refers to the accumulation of sucrose in the internodes. In Ethiopia, sugar content in cane is normally lowest in the start of the crushing period (lack of complete drying of the soil due to rain prior to cane crushing) and late period (due to the prevailing high temperature). The potentiality of the problem most probably will prevail in the lowland regions of the country where temperature is high in both the early and late periods (Tadesse, 2006).

Profit maximization is a must to be viable in the competitive global market. Thus, the sugar sector is making a remarkable effort to maximize profit through increasing sugar production per unit area. Among the less attention given challenges, low recovery of sucrose in the early and late periods of cane crushing is emerging to be the focus of the sector. Furthermore, the increase in temperature due to climate change (Srivastava and Rai, 2012) coupled with the high cost of production of sugar makes the industry incompetent in the world market. Thus, increasing sugar yield per unit area is identified as an opportunity. In Ethiopian sugar industry, attaining high sucrose content is the prime and critical objective of cane cultivation among others.

METHODOLOGY

Sugar Factories Considered

Three sugar factories located in the Rift Valley regions of Ethiopia were considered from which Wonji-Shoa and Metahara are currently producing sugar and have different physiographic set-up, while Tendaho Sugar Factory is a new sugar factory to commence crushing soon (Table 1). Furthermore, the remaining sugar factory Finchaa and newly emerging sugar factories geographic location and meteorological information is described on Table 2.

Data acquisition

Cane plantation production data from 2005/6-2009/10 were used to study the sucrose recovery trend of Wonji-Shoa and Metahara Sugar Estates to elucidate the sucrose recovery trend. For rainfall and temperature trend analysis, the meteorological data collected and documented for the respective years (2005/6-2009/10) were used. However, for Tendaho, since the factory is new, mean values for sucrose yield from two experiments and meteorological data were used. For Finchaa sugar factory and newly emerging sugar projects only geographic and climatic data were used from the respective stations and other sources (Table 2). Loss in sucrose percent cane (%) was calculated as the deviation from the peak value attained in the cane crushing months (February for Wonji-Shoa and December for Metahara). To substantiate the content, different publications were reviewed. Especially the South African research findings were used broadly in the review due to their rich experiences in relation to sugarcane ripeners' management. The data

_Published by European Centre for Research Training and Development UK (www.eajournals.org)

was analyzed using Excel-data sheet for plotting charts of sucrose yield and meteorological parameters (rainfall and temperatures).

Table 1. Meteorological and geographic information of Wonji-Shoa, Metahara and Tendaho sugar factories

Factory	Geographic Location	Altitude	RF	Temperature (⁰ C)		
		(m.a.s.l)	(mm)	Min.	Max.	Mean
Tendaho	11°_{45} 30 [°] - 11°_{10} 50 [°] N and $40^{\circ}_{45^{\circ}}$ - 41°_{10} 03 [°] E	365 to 340	222	21.9	37.2	29.6
Metahara	$8^{0}51$ N and $39^{0}52$ E	950	554	17.5	32.6	25.1
Wonji-Shoa	8°31'N and 39°12'E	1550	800	15.3	26.9	21.1

Note: *RF*=*rainfall; m.a.s.l*= *meter above sea level; mm*= *millimeter; Min*=*minimum; Max*=*maximum.*

Table 2. Meteorological and geographic information of Finchaa Sugar Factory and newly emerging Sugar Factories (Kessem, Wolkait, Kuraz, Arjo-Dedessa and Beles)

Factory	Geographic Location	Altitude	Rainf	Temperature (⁰ C)		
		(m.a.s.l)	all	Min.	Max.	
			(mm)			Mean
Finchaa	8°31'N and 39°12'E	1350-1650	1300	15.0	31.0	23.0
Kessem	39° 54' E and 09° 09' N	800 to 850	569	18.9	34.2	26.6
Wolkait	13°50' N and 37°35' E	725**	910	19.5	35.5	27.5
Kuraz	$5^{\circ}8'$ to $6^{\circ}16'$ N and $35^{\circ}43'$ -	400	991	20.2	34.9	27.6
	36°13' E					
Arjo-	$8^{\circ}30$ ' to $8^{\circ}40$ ' N and $36^{\circ}22$ '	1350	1400	20.5	25.4	23.0
Dedessa	to 36 ⁰ 43' E					
Beles	$11^{0}30$ N and $36^{0}41$ E	1110	1447	16.4	32.5	24.5

Note: *RF*=*rainfall; m.a.s.l*= *meter above sea level; mm*= *millimeter; Min*=*minimum; Max*=*maximum.*

**Source: Google earth.

RESULT AND DISCUSSION

Sucrose percent cane pattern at Wonji-Shoa and Metahara Sugar Estates

Analysis result of five consecutive years (2005/06-2009/10) for sucrose percent cane across the crushing months at both sugar estates showed a sigmoid curve indicating a decline in sucrose content of cane at the start and end periods of cane crushing (Figure 1). The declining trend in sucrose value in the starting period of crushing (Figure 1) is conspicuously arises from the residual moisture in the soil from the main rainy season (June-September). However, in the late

_Published by European Centre for Research Training and Development UK (www.eajournals.org)

period of cane crushing principally, the prevailing high temperature combined with the intermittent rainfall plays a role in the decline of sucrose content of cane.

The temperature and rainfall pattern of the two sugar estates are shown in Figure 2. At both sugar estates (Figure 2A and 2B), in the early cane crushing season the crop experiences low sucrose content. This is due to the presence of residual moisture from the previous months (June to September). The presence of enough moisture in the soil reduces sucrose content of cane (Donaldson and Bezuidenohout, 2000). At both Sugar Estates withholding irrigation (drying-off) is the conventional practice under use. This practice has limitations in enhancing the sucrose content of cane in the early period of crushing, due to the lack of complete drying of the soil prior to harvest. In contrary to this, in the late period of crushing, the relatively higher prevailing temperature reduces sucrose content of cane since cane growth is favoured (Gawander, 2007).



ure 1. Average sucrose yield (%) of harvested cane from 2005/6-2009/10 and 2005/6-2009/10 cropping seasons at Metahara (A) and Wonji-Shoa (B) Sugar Estates, respectively.



_Published by European Centre for Research Training and Development UK (www.eajournals.org)

Figure 2. Average minimum and maximum temperatures and rainfall pattern of Metahara (A) and Wonji-Shoa (B) Sugar Estates from 2005/6-2009/10 cropping seasons.

The highest mean sucrose percent canes were obtained in the months of February and December at Wonji-Shoa and Metahara; respectively (Figure 1). The decrease in sucrose percent cane in the early and late periods from the peak value attained in the cool period indicates the loss that occurs during the crushing months. In general a mean sucrose loss of 0.53 and 0.54 is observed at Wonji-Shoa and Metahara; respectively (Table 3).

Wonji-Shoa				Metahara			
Months	Sucrose (%)	Peak Sucrose (%)	Sucros e Loss (%)	Months	Sucros e (%)	Peak Sucrose (%)	Sucrose Loss (%)
October	10.43	11.38	0.95	October	12.11	12.52	0.41
November	10.69	11.38	0.70	November	12.35	12.52	0.18
December	10.95	11.38	0.44	January	12.37	12.52	0.15
January	11.17	11.38	0.21	March	12.20	12.52	0.32
March	11.36	11.38	0.02	April	11.94	12.52	0.59
April	10.97	11.38	0.41	May	11.48	12.52	1.04
May	10.8	11.38	0.58	Jun	11.42	12.52	1.10
Jun	10.49	11.38	0.89				
Mean Loss			0.53	Mean Loss			0.54

Table 3. Estimated loss in sucrose percent cane during the crushing months against the peak attained in February and December at Wonji-Shoa and Metahara Sugar Factories, respectively.

The mean day temperatures of Wonji-Shoa and Metahara sugar estates are therefore 21.1 and 25.1 0 C, respectively (Table 1 and Figure 2). In line with this Gururaj (2001) stated that a mean day temperature of 12-14 is desirable for proper ripening. Thus, the enhanced temperature at Wonji-Shoa and Metahara resulted in a lower sucrose recovery (Figure 1). Furthermore, the relatively higher mean daily temperature at Metahara (25.05 0 C) has resulted in a lower sucrose recovery as compared to Wonji-Shoa (21.10 0 C) (Figure 1 and 2).

Sucrose percent cane at Tendaho Sugar Factory

Though there has been no data on commercial harvesting at Tendaho Sugar Factory, from the experiments conducted, the presence of ripening problem can be deduced (Table 4). The first experiment entitled with effect of age of seed cane on yield and yield components of sugarcane at Tendaho sugar factory (Experiment 1) was harvested in the month of December at 12 months of age, while the second experiment was effect of number of buds per sett and intra-row spacing of setts on yield and yield components of sugarcane (Experiment 2) was harvested in the month

_Published by European Centre for Research Training and Development UK (www.eajournals.org)

of September at age of 12 months. The temperature and rainfall patterns experienced during the study periods are illustrated on Figures 3. The mean sucrose percent cane obtained averaged for the main effects of the varieties was 7.85 and 6.78; for experiment 1 and 2 respectively.

 Table 4. Mean values of sucrose percent cane of sugarcane varieties obtained from two

 experiments conducted at Tendaho Sugar Factory at 12 months of age

December Harvesting (Experiment 1)		August Harv	August Harvesting			
		(Experiment	: 2)			
Varieties	Sucrose (%)	Varieties	Sucrose (%)			
B52298	8.86	Co680	6.60			
NCo334	7.36	N14	6.85			
Mex 45/245	7.33	Co740	6.89			
Mean	7.85	Mean	6.78			

Minimum Temperature 60 100 Maximum Temperature Temperature (⁰C) 50 Rainfall (mm) 75 40 Rainfall 30 50 20 25 10 0 0 Aug Sep Jun Apr Jan Eb Mar May E Oct Nov Dec Months (A)Minimum Temperature 60 100 Maximum Temperature Temperature (⁰C) 50 Rainfall (mm) 75 Rainfall (mm 40 30 50 20 25 10 0 0 Aug Jan Feb Apr Vlay Jun Sep Oct Vov Mar E Dec

Note: Experiment 1 = Netsanet *et.al* (2014); Experiment 2 = Netsanet (2009).

Figure 3. Average minimum and maximum temperatures and rainfall pattern of Tendaho on the studies of effect of age of seed cane on yield and yield components of sugarcane from January, 2012-December, 2013 (A) and effect of number of buds per sett and intra-row spacing from September 2007 to August 2008 (B).

Months

(B)

_Published by European Centre for Research Training and Development UK (www.eajournals.org)

In both experiments percent recoverable sucrose was poor (Table 5). The mean sucrose percent cane from the three varieties in experiment 1, in general, ranged from 7.33 to 8.86% and was higher than that of experiment 2 which ranged from 6 to 6.89%. The relatively higher percent sucrose cane in experiment 1 was due to the relatively low temperature and absence of rainfall during the months of October and November (Figure 3A). The mean day temperatures recorded during the ripening period prior to harvest in October and November were 38.4 and 31.5 °C, respectively; however, in the second experiment the mean day temperatures for July and August was 32.75 °C. In contrary to this, Legendre (1975) asserts that temperatures of 17-18 °C appear to be favorable for the partition of photosynthates into the internodes and the accumulation of sucrose. On the other hand Gururaj (2001) states that for proper ripening a mean day temperature of 12-14 °C is desirable, since at higher temperature during ripening, inversion takes place with considerably reduced sugar recoveries.

Possible challenges at Finchaa and newly emerging sugar factories

The climatic condition prevailing at Finchaa and the newly emerging sugar projects of the country indicates the possibility of challenges in ripening as it can be judged from the mean daily temperature and rainfall data (Table 2). The mean day temperature in general ranges from 23.0 to 27.6 ^oC. The temperatures are higher than the mean day temperature range required for maximum accumulation of sucrose (Gururaj, 2001; Legendre, 1975). Furthermore, the presence of rain would also contribute its share for the decrease especially after the main rainy season in a similar way as Wonji-Shoa and Metahara Sugar Factories. The rainfall experienced in all these locations (Table 4) is higher than Wonji-Shoa, Metahara and Tendaho (Table 2).

CONCLUSION

This study has clearly displayed the problem of natural sugarcane ripening in some of the sugar factories of the country with concrete evidences. Research and developments made abroad showed the possibility of solving the problem of ripening in the early and late periods of cane crushing by using chemical ripeners. Some studies conducted in Ethiopia also indicated the presence of response, though inconclusive and further work is required. The appreciation of the ripening problem needs to be the point of departure for successful integration of sugarcane ripeners. Thus, it is emphasized that the presence of low recovery in the early and late periods of crushing is a conspicuous challenge of the sugar factories.

REFERENCES

Anonymous (ND). Sugar and Sugarcane, Chapter 3. (Cited on April 7, 2014: http://etd.lsu.edu/docs/available/etd-0228103-142646/unrestricted/03%20Sugarcane% 20and%20Sugar.pdf

Published by European Centre for Research Training and Development UK (www.eajournals.org)

- Batta SK, Kaur S, Mann APS (2002). Sucrose accumulation and maturity behaviour in sugarcane is related to invertase activities under subtropical conditions. *Sugarcane Intl.*, Jan- Feb 10–13.
- Donaldson RA, Bezuidenhout CN (2000). Determining the maximum drying off periods for sugarcane grown in different regions of the South African Industry. *Proc S Afr Sug Technol Ass* 74: 162-166.
- Gawander J (2007). Impact of climate change on sugar-cane production in Fiji. WMO Bull. 56 (1).
- Gosnell JM, Lonsdale JE (1974). Some effects of drying off before harvest on cane and yield quality. *Proc Int Soc Sug Cane Technol* 15:701-711.
- Gururaj H (2001). Sugarcane in Agriculture and industry. Prism Books Pvt Ltd. Bangalore. India.
- Humbert PR (1968). The growing of sugarcane. Elsevier Publishing Company, New York.
- James G (ed) (2004). Sugarcane. Blackwell Science Ltd. UK.
- Legendre BL (1975). Ripening of sugarcane: effects of sunlight, temperature, and rainfall.
- *Crop Science*, 15(3):349-352.
- Orgeron AJ (2003). Planting rate effects on sugarcane yield trials. A Thesis Submitted to the Graduate Faculty of Louisiana State University and Agricultural and Mechanical College in partial fulfillment of the requirements for the degree of Master of Science.
- SASRI (2008). South Africa Sugarcane Research Institute The Link. Volume 17, Number 1. South Africa.
- Singles A, Kennedy AJ, Bezuidenhout CN (2000). The effect of water stress on sugarcane biomass accumulation and partitioning. *Proc S Afr Sug Technol Ass.* **74**:169-172.
- Srivastava AK, Rai MK (2012). Sugarcane Production: Impact of climate change and its mitigation (Review). *Biodiversitas*. **13(4):**214-227.
- SSATS (2003). Swaziland Sugar Association Technical Services. Chemical Ripener Recommendations. Extension Newsletter. No 27, 4th Quarter. Swaziland.
- Sundara B (2000). Sugarcane cultivation. Vikas publishing house Pvt. ltd., New Delhi.
- Tadesse Negi (2006). Prefeasibility Study on the application of sugarcane ripener at Metahara (A preliminary Research Report). An investigation conducted in collaboration with Project and productivity improvement office, Metahara Sugar Factory, Wonji. Ethiopia.